DOCUMENT RESUME

ED 097 517 CE 002 287

TITLE Aircraft Sheet Metal General Repairs; Sheet Metal

Work 3: 9857.01.

INSTITUTION Dade County Public Schools, Miami, Fla.

PUB DATE Apr 73

NOTE 18p.; An Authorized Course of Instruction for the

Quinmester Program

EDRS PRICE MF-\$0.75 HC-\$1.50 PLUS POSTAGE

DESCRIPTORS *Aviation Mechanics; Behavioral Objectives; Course Content; Course Descriptions; *Curriculum Guides; Grade 12; Job Skills; *Metal Working Occupations;

Secondary Grades; *Sheet Metal Work; Shop Curriculum; Skill Development; *Trade and Industrial Education;

Vocational Education: Welding

IDENTIFIERS *Quinmester Program

ABSTRACT

The outline will serve as a guide to the high school student interested in the field of sheet metal work. Intended for the 12th grade level, the course is organized into three instructional blocks: (1) general repairs, (2) line maintenance, (3) brazing and soldering, followed by a posttest. The advanced course is 135 hours in length and offers instruction in sheet metal techniques in manufacturing and repairing miscellaneous parts for aircraft and shop equipment. A bibliography lists basic and supplementary reference materials and films. A posttest sample concludes the course description. (MW)



BEST COPY AVAILABLE

U S DEPARTMENT OF HEALTH.

EDUCATION & WELFARE
NATIONAL INSTITUTE OF
EDUCATION

THIS DOCUMENT HAS BEEN REPRO
DUCED EXACTLY AS RECEIVED FROM
THE PERSON OR ORGANIZATION ORIGIN
ATING IT POINTS OF VIEW OR OPINIONS
STATED DO NOT NECESSARILY REPRE
SENT OFFICIAL NATIONAL INSTITUTE OF
EDUCATION POSITION OR POLICY

AUTHORIZED COURSE OF INSTRUCTION FOR THE



Course Outline SHEET METAL WORK 3 - 9857 (Aircraft Sheet Metal General Repairs) Department 48 - Quin 9857.01

ERIC

DIVISION OF INSTRUCTION-1973

DADE COUNTY PUBLIC SCHOOLS 1450 NORTHEAST SECOND AVENUE MIAMI, FLORIDA 33132

Course Outline

SHEET METAL WORK 3 - 9857 (Aircraft Sheet Metal General Repairs)

Department 48 - Ouin 9857.01

county office of
VCCATIONAL AND ADULT EDUCATION



THE SCHOOL BOARD OF DADE COUNTY

Mr. G. Holmes Braddock, Chairman
Mr. William H. Turner, Vice-Chairman
Mrs. Ethel Beckham
Mrs. Crutcher Harrison
Mrs. Phyllis Miller
Mr. Robert Renick
Dr. Ben Sheppari

Dr. E. L. Whigham, Superintendent of Schools
Dade County Public Schools
Miami, Florida 33132

April, 1973

Published by the School Board of Dade County



Course Description

9857
State Category
Number
Number

48
9857.01
County Dept.
Number
Aircraft Sheet Metal General Repairs
County Course
Number
Course Title

This is an advanced quinmester course in sheet metal techniques in manufacturing and repairing miscellaneous parts for aircraft and shop equipment. Use of brazing and soldering equipment will be included. This is a three quinmester credit course.

Indicators of Success: Prior to entry into this course, the student will display mastery of the skills indicated in 9855.01.

Clock Hours: 135



PREFACE

The following quinmester course outline will serve as a guide to the high school student who wishes to pursue the field of sheet metal work.

This is a first quinmester course for the twelfth grade.

This course outline consists of four blocks of instruction which are subdivided into several units each. The course is 135 hours in length.

Prior to entry into this course the student must display mastery of the skills indicated in Quin 9855.01.

Great emphasis will be placed on the use of visual aids, mock-ups, cutaways, transparencies, films, instructional sheets and manipulative shop practice.

This outline was developed through the cooperative efforts of the instructional and supervisory personnel, the Quinmester Advisory Committee, and the Vocational Curriculum Materials Service, and has been approved by the Dade County Vocational Curriculum Committee.



TABLE OF CONTENTS with Suggested Hourly Breakdown

	•	Page
	E	i
		iii
SPECIFIC BLOCK OBJECTIVES		
BIBLIO	GRAPHY	. 3
BLOCK		
I.	GENERAL REPAIRS (60 Hours)	
	Repairing Miscellaneous Parts	1
	Manufacturing and Repairing Shop Equipment	1
	Making Modification on Aircraft	1
II.	LINE MAINTENANCE (60 Hours)	
	Making Repairs as Needed	1
	Interpreting Specifications	1
III.	BRAZING AND SOLDERING (15 Hours)	
	Brazing Steel Parts	2
	Silver Soldering	2
	Soft Soldering	2
IV.	QUINMESTER POST-TEST	
APPENDI	IX: OUINMESTER POST-TEST SAMPLE	5



GOALS

The student must be able to demonstrate:

- 1. The skills and knowledge necessary to do aircraft sheet metal general repairs.
- 2. Ability to manufacture and repair shop equipment.
- 3. Ability to perform line maintenance aircraft general repairs.
- 4. Ability to refer to federal aviation administration publication and interpret their meanings.
- 5. Skills used for sheet metal repairs.
- 6. Ability to do simple brazing and soldering operations.



SPECIFIC BLOCK OBJECTIVES

BLOCK I - GENERAL REPAIRS

The student must be able to:

- 1. Demonstrate the ability to make general repairs on the aircraft.
- 2. Exhibit the ability required in manufacturing and repairing shop equipment.
- 3. Exhibit the ability required in making modification in aircraft and interpret specifications for modifications.

BLOCK II - LINE MAINTENANCE

The student must be able to:

- 1. Exhibit the ability to do general repairs on the line maintenance aircrafts and equipments.
- 2. Exhibit the skills and knowledge to interpret specification set forth by the F.A.A. and the aircraft manufacture.

BLOCK III - BRAZING AND SOLDERING

The student must be able to:

- 1. Demonstrate the ability to do simple brazing operations.
- 2. Demonstrate the ability to do simple soldering operations.
- 3. State the hazards of brazing and soldering.

BLOCK IV - QUINMESTER POST-TEST

The student must be able to:

1. Satisfactorily complete the quinmester post-test.



Course Outline

SHEET METAL WORK 3 - 9857 (Aircraft Sheet Metal General Repairs)

Department 48 - Quin 9857.01

I. GENERAL REPAIRS

- A. Repairing Miscellaneous Parts
 - 1. Doors
 - 2. Hatches
 - 3. Wash room
 - 4. Decking
 - 5. Seats
 - 6. Hinges
 - 7. Door hatches
 - 8. Galley
 - 9. Brackets and fixtures
 - 10. Cowling
 - 11. Firewall
 - 12. Instrument panel
- B. Manufacturing and Repairing Shop Equipment
 - 1. Making metal containers
 - a. Waste cans
 - b. Parts pans
 - c. Parts wash pan
 - d. Tank
 - 2. Making metal utility items
 - a. Funnels
 - b. Tool kit boxes
 - c. Hose carts
 - d. Ladder and steps
 - e. Air ducts
- C. Making Modification on Aircraft
 - 1. Interpreting federal publication and specification
 - 2. Interpreting manufacturer's manuals and specification

II. LINE MAINTENANCE

- A. Making Repairs as Needed
 - 1. Repairing flight controls
 - 2. Repairing air frame damage
 - -3. Repairing Nacelles and cowling
 - 4. Repairing hulls, tanks and floats
- B. Interpreting Specifications
 - 1. Complying with F.A.A. requirements
 - 2. Complying with manufacturer's recommendations and specifications



III. BRAZING AND SOLDERING

- A. Brazing Steel Parts
 - 1. Preparation of material for brazing
 - 2. Function and application of flux
 - 3. Special techniques used in brazing
 - 4. Use of brazing in aircraft repairs
- B. Silver Soldering
 - 1. Preparation of parts for silver soldering
 - 2. Function and application of flux
 - 3. Special techniques used in silver soldering
 - 4. Use of silver in aircraft parts
- C. Soft Soldering
 - 1. Soldering copper
 - 2. Tinning the copper
 - 3. Types of soft solder
 - 4. Soldering techniques
 - 5. Post soldering treatment
- IV. QUINMESTER POST-TEST



BIBLIOGRAPHY (Aircraft Sheet Metal General Repairs)

Basic Reference:

None

Supplementary References:

- 1. Aero Publishers. Maintenance and Repair of Aerospace Vehicles.
 3rd ed. New York: McGraw-Hill Book Company, Inc., 1963.
 Pp. 320.
- 2. <u>Airframe Mechanic Written Exam Guide</u>. Fort Worth, Texas: Arme School of Aeronautics, 1968. Pp. 63.
- 3. Alcoa Aluminum Handbook. Pittsburg: Aluminum Company of America, 1959. Pp. 222.
- 4. Boggess, Edward. Aircraft Sheet Metal Work. New York: Pitman Publishing Company, 1941. Pp. 117.
- 5. Forming Manual. Salt Lake City: Utah State Board of Vocational Education, 1942. Pp. 298.
- 6. Frazer, Russell. <u>Practical Aircraft Sheet Metal Work</u>. New York: McGraw-Hill Book Company, Inc., 1942. Pp. 193.
- 7. Giachino, J. W. Aircraft Sheet Metal Work. Peoria, Illinois: The Manual Arts Press, 1942. Pp. 123.
- 8. Leavell, Stuart, and Bungay, Stanley. <u>Standard Aircraft Handbook</u>. Los Angeles: Aero Publishers, Inc., 1952. Pp. 159.
- 9. Lemaster, Clarence Allen. <u>Aircraft Sheet Metal Work</u>. Chicago: American Technical Society, 1944. Pp. 117.
- 10. Nista, Albert H. <u>Aircraft Riveting</u>. New York: McGraw-Hill Book Company, Inc., 1942. Pp. 160.
- 11. Norcross, Carl. <u>How To Do Aircraft Sheet Metal</u>. New York: McGraw-Hill Book Company, Inc., 1942. Pp. 228.
- 12. Northrup Institute of Technology. Aircraft Maintenance and Repair.
 New York: McGraw-Hill Book Company, Inc., 1955. Pp. 444.
- 13. Overby, Charles A. <u>Aircraft and Missile Design Maintenance Handbook</u>. New York: The Macmillan Company, 1960. Ip. 320.
- 14. Rice, Ralph. <u>Aero Mechanics Questionnaire</u>. Los Angeles: Aero Publishers, Inc., 1955. Pp. 238.



- 15. Template Layout. Glendale, California: Aero Publishers, 1942.
 Pp. 306.
- 16. United States Department of Air Force. Air Frame Maintenance.
 Air Force Manual 52-11. Washington, D.C.: United States
 Government Printing Office, 1964. Pp. 314.
- 17. United States Naval Air Technical Training Command. Aircraft
 Structural Maintenance, Naupers 10308B. Washington, D.C.:
 United States Government Printing Office, 1969. Pp. 414.

Films:

- 1. Airframe Mechanic, The. 16 mm. 10 min. B/W. Sound. 1959.

 Jam Handy.
- 2. Airplane Structures. 16 mm. 45 min. B/W. Sound. 1945. Jam Handy.
- 3. Building PBY. 16 mm. 45 min. B/W. 1943. Consolidated Aircraft Corporation.
- 4. Forming Aluminum. 16 mm. 20 min. B/W. 1966. Alcoa.
- 5. How To Rivet Aluminum. 16 mm. 20 min. B/W. 1942. Alcoa.

APPENDIX

Quinmester Post-Test Sample



Name	Date Sco	re _	
Only	Multiple Choice Test Items Each statement needs a word, a figure, or a phrase to make it composed one of the choices listed is correct. Place the number of the	rrec:	t. ce
you	make in the space provided at the right edge of the sheet.		
1.	Aircraft metal work is usually called sheet metal work. What is the difference between sheet and plate? (1) Sheet can be formed by hand and plate cannot, (2) Composition of metal, (3) Depends only on where it is used, (4) Thickness only		<u> </u>
2.	Fuel tanks should be constructed capable of withstanding an internal pressure of: (1) 3-1/2 ps1, (2) 5 ps1, (3) 2-1/2 ps1 (4) 15 ps1.	l,)
	In bending sheet metal it is important that, if possible, it is to be bent: (1) 180° to the grain, (2) across the grain, (3) 45° to the grain, (4) parallel to the grain.	;)
	A sheet metal technician is to repair a damaged aircraft spar, he must do the work in accordance with the instructions contained in the: (1) repair manual for the applicable spar, (2) manufacturer's structural handbook, (3) structural repair manual for the applicable aircraft, (4) general structural repair manual.	3-)
	If you discover a crack in the web of a bulkhead, you should use the same type repair as you would use: (1) on fully stressed skin, (2) on lightening hule repairs, (3) on staingers and longerons, (4) if the web were buckled.	()
	The beads on a former rib serve what purpose? (1) They lighten the rib, (2) They reinforce the flange, (3) They keep the flangid, (4) they stiffen the web.	ige ()
	Which of the following is an advantage of the use of a former ribrather than a truss or reinforced rib? (1) It is lighter, (2) It is stronger, (3) It does not require lightening holes, (4) It is more adaptable for use in larger aircraft.	()
	The term brazing includes all but which of the following processe (1) Bronze welding, (2) Hard soldering, (3) Silver soldering, (4) Stainless steel welding	es?)
1	For brazing a joint in metal with a melting point of 1, 87° F, yo should not use brazing alloy of graze? (1) A, (2) B, (3) C, (4) D	น	

- In brazing, flux must be added to the: (1) hot filler rod, (2) hot base metal, (3) cold filler rod, (4) cold base metal. 11. A joint should not be brazed under which of the following conditions: (1) the base metal has too high a melting point, (2) the finished joint must withstand very high temperatures, (3) the metals to be joined are not the same, (4) the metals to be joined have been heat treated. () When brazing brass you must be very careful to prevent the required oxidizing torch flame from burning which component of the alloy: (1) tin, (2) lead, (3) zinc, (4) copper.) 13. The filler rod used for brazing brass should have a melting point of approximately: (1) $1,450^{\circ}$ F, (2) $1,600^{\circ}$ F, (3) $1,700^{\circ}$ F, (4) 1,800° F. () Class (3) solder used to join two sheets of 1/8" copper contains silver, copper, and: (1) zinc, (2) nickel, (3) phosphorus, (4) cadmium.) When the flux becomes liquid, the solder will flow when its temperature has been raised an additional: (1) 100° F, (2) 200° F, (3) 270° F, (4) 300° F.) 16. In a lap joint, for strength equal to that of the base metal in the heater zone, the amount of lap should be: (1) 2 to 4 times the metal thickness, (2) 3 to 5 times the metal thickness, (3) 4 to 6 times the metal thickness, (4) all of the above.) Which type of torch flame is preferred for silver soldering: (1) soft neutral, (2) harsh neutral, (3) soft carburizing, (4) harsh carburizing. () 18. If an electrical connection that has been sealed with soft solder is accidentally placed under steady tension, the solder is likely to: (1) increase the electrical resistance of the circuit, (b) melt after a long period of use, (3) strengthen the connection and prevent failure, (4) yield and produce failure. () Before being used, a soldering copper must be tinned in order to: (1) reshape the point, (2) sharpen the surface of the point, (3) place a thin film of solder over the entire surface of the point, (4) place a thin film of oxide on the surface of the point. ()
- 20. Why is resin flux commonly used for soldering electrical connections: (1) to prevent corrosion caused by residual traces of flux, (2) to prevent contamination of the soldering iron, (3) to dissolve oxides from the solder and the work, (4) to harden the solder and prevent breakage.

- 21. The process whereby two surfaces that have been previously tinned are joined and heated, causing the solder to run together and form a joint is called: (1) hard soldering, (2) dual soldering, (3) sweating, (4) dual tinning.) 22. How should you remove the flux from copper alloy that has been soft soldered? (1) Sandblast it lightly, (2) Boil it in caustic soda solution, (3) Rinse it thoroughly with fresh, cold water, (4) Place it in a solution of sulfuric acid, sodium bichromate, and water. () Which of the following mixtures will restore the original color to the copper? (1) Sulfuric acid, nitric acid, hydrochloric acid and water, (2) Sulfuric acid, nitric acid, sodium bichromate and water, (3) Sulfuric acid, sodium bichromate and water, (4) Caustic soda and water () 24. You are using 1/8 inch rivets on a metal surface patch and using a single row pattern. What is the minimum acceptable overlap of the patch: (1) 3/4 inch, (2) 1 inch, (3) 1/2 inch, (4) 7/8 inch. () 25. When repairing a tear in stressed skin, the major consideration of the repair is: (1) to use material one size thicker, (2) the shear strength of the material, (3) to use the same rivet spacing as the nearby riveting, (4) to use one size larger rivet. Bending a piece of metal until it almost reaches the breaking point is its: (1) minimum bend radius, (2) maximum bend radius, (3) maximum bend allowance, (4) minimum bend allowance. () 27. How many AN 470 ad-4-6- rivets will be required to attach a 10" x 5" splice plate if you use a single row pattern, minimum edge distance and 4d spacing? (1) 60 rivets, (2) 56 rivets, (3) 62 rivets, (4) 52 rivets ()
- 28. You plan to use 1/8 inch diameter universal rivets to rivet together two pieces of .0625" thickness material. What should be the minimum length of the rivet? (1) 5/16 inch, (2) 1/4 inch, (3) 1/8 inch, (4) 7/16 inch
- 29. A.D. notes are mandatory airworthiness directives set forth by whom?
 (1) Manufacturer's manuals, (2) F.A.R Part #39, (3) F.A.R. aircraft listing, (4) Manufacturer's service bulletins
- 30. "ALCLAD" aluminum is: (1) pure aluminum coated with an aluminum, (2) aluminum alloy coated with pure aluminum, (3) pure aluminum, (4) aluminum alloy only
- 31. Which of the following documents has now replaced the old Aircraft Specification? (1) aircraft operations manual, (2) F.A.A. air directives, (3) aircraft inspection and repair, (4) type certificate data sheets



- 32. If an assembly is to be heat treated and joined by riveting, when should the riveting operations be done? (1) Before heat treatment, (2) during the heat treatment process, (3) after heat treatment, (4) rivet partially then heat treat
- 33. Brazing is different from welding in that: (1) welding you use a torch and brazing you use an iron, (2) welding you use flux and brazing doesn't use flux, (3) brazing melts the base metal, welding does not, (4) welding melts the base metal, brazing does not.

ANSWER KEY TO QUINMESTER POST-TEST

- 1. (4)
- 2. (1)
- 3. (2)
- 4. (3)
- 5. (1)
- 6. (4)
- 7. (1)
- 8. (4)
- 9. (4)
- 10. (1)
- 11. (2)
- 12. (3)
- 13. (2)
- 14. (1)
- 15. (4)
- 16. (3)
- 17. (1)

- 18. (4)
- 19. (4)
- 20. (1)
- 21. (3)
- 22. (4)
- 23. (1)
- 24. (3)
- 25. (3)
- 26. (1)
- 27. (2)
- 28. (1)
- 29. (2)
- 30. (2)
- 31. (4)
- 32. (3)
- 33. (4)

